

# M-SERIES

## DIGITAL MIC/VOICE PROCESSORS


### DIGITAL MIC/VOICE PROCESSOR M-1



### 2-CHANNEL DIGITAL MIC/VOICE PROCESSOR M-2



### 4-CHANNEL DIGITAL MIC/VOICE PROCESSOR BLADE M-4IP



### 4-CHANNEL DIGITAL MIC/VOICE PROCESSOR BLADE-3 M-4IP3



## **Wheatstone Processing**

Whether it's a single voice or every piece of audio in your facility, Wheatstone believes that you should have the power to shape your OWN sound – one with a completely unique sonic signature that's your sound, not the one created by a processor manufacturer.

To achieve this goal Wheatstone has developed Vorsis Ultra-High Resolution Processing technology to provide completely clean, high quality 'draw you in' sound that even the best ears in the business love to hear. This proven Vorsis technology is embedded in every Wheatstone processor to create the cleanest sound, as loud as you want it.

We think Wheatstone's Vorsis Ultra-High Resolution Processing is the best you'll ever use. But don't take our word for it. Try it out. We CAN guarantee you'll be happy you did!



# M-1 mic/voice processor

experience YOUR voice enhanced by great processing



The M1 is a flexible digital microphone processor. It offers unlimited presets, security and networkability in an all-digital framework, with parameters that are easy to set up. Either from the front panel, or from the GUI - all parameters of the M1 can be controlled to give each voice talent his or her own personal sound at the press of a button.

The M1 microphone processor is equipped with a Super-Quiet (SQ) microphone preamplifier featuring an extremely low noise floor, very wide dynamic range, faithfully accurate transient response, and ruler flat frequency response. Operating in harmony with high quality 24-bit A/D converters and a 96kHz base sample rate, the M1 adds absolutely no undesired coloration to the signal and faithfully preserves the sound of any microphone and talent combination.

The features on the M1 include four-band parametric EQ, high- and low-pass filters, de-esser and expander and of course, our proprietary Vorsi dynamics processing. The unit comes loaded with factory designed presets, and designing your own is easy, thanks to features such as "Quick Save" and "Quick Compare" that allow you to toggle back and forth between different presets as you adjust them. From one GUI, an entire group of M1's can be controlled, making multiple microphone processor management easy.

## Wheatstone-designed EQ

Very high quality parametric and shelving equalization is available to sweeten the sound of any microphone as desired without adding noise or undesirable artifacts to the signal.

## Wheatstone-designed Dynamics Control

A high performance de-esser and a smooth sounding, very low distortion compressor/limiter dynamics control section round out the M1's offerings to create powerful and authoritative presence on production or on-air microphones.




**Wheatstone Talent Control Interface and GUI**

Voice talent can activate his or her own personal sound at the press of a button using the Talent Control Interface, a special GUI designed for preset recall only. The Wheatstone Talent Control Interface software can reside on an air studio/control room PC and gives talent the ability to recall presets from any Wheatstone microphone processor without allowing processing adjustments. It also offers a high-resolution display of input and output levels as well as an FFT display of the talent’s voice either pre or post processing.

All parameters of the M1 are adjustable using the included Windows-based GUI which can control as many as 254 M-1 devices (see page 10).


- Control of all audio parameters
- Intuitive PC graphical user interface (GUI)
- High quality, low noise microphone preamp
- Phantom power
- Metering: In/Out, de-esser, compression, expansion
- Password based security
- 44.1, 48 or 96 kHz AES3 output sample rates
- Mic or line level out, selectable from rear panel
- 24-bit A/D, D/A converters
- Preset storage/recall via GUI
- Variable frequency de-esser
- Voice phase rotator
- Adjustable compression
- Downward expansion
- EQ: two-band parametric plus variable high and low shelving
- Tunable high and low pass filters
- FFT voice energy display via GUI
- Quick save/compare function
- TCP/IP Ethernet remote control
- Takes up only one rack space
- Front panel controls can be locked out via rear dipswitch

**M-1 BLOCK DIAGRAM**



# M-2 dual-channel mic/voice processor

double your pleasure by processing two voices at once



The M2 is a dual-channel DSP-based voice processor. The M2 is able to operate in completely independent dual channel mode or, at the touch of a button, M/S mode for professional stereo recording applications.

The M2 microphone processor is equipped with twin, matched Super-Quiet (SQ) microphone preamplifiers featuring extremely low noise floor, very wide dynamic range, faithfully accurate transient response, and ruler flat frequency response. Operating in harmony with high quality 24-bit A/D converters and a 96kHz base sample rate, the M2 adds absolutely no undesired coloration to the signal and faithfully preserves the sound of any microphone and talent combination. It features twin high-bandwidth, very low noise microphone preamplifiers, a four-section equalizer with high and low shelving EQ and two bands of fully parametric EQ, high and low pass filters, de-esser and expander functions.

The signal path of the M2 may be operated as a dual channel microphone processor with completely independent channels or as an M/S pair for use in professional high-quality, crossed-microphone M/S recordings. Included in the M2 dual-channel voice processor is Wheatstone's smooth-sounding Vorsis dynamics processing, configurable to up to three bands of processing. Adjustable from anywhere on your network, the M2 offers the security of password protected TCP/IP-based remote control and no front panel controls.

## Wheatstone-designed Equalization

Based on great-sounding designs built for Wheatstone's high performance professional audio applications, the M2's equalization section operates predictably and adds no noise, ringing, phasiness or other undesirable coloration to the sound.

## Wheatstone-designed Dynamics Processing tools

A high performance and fully adjustable downward expander, de-esser, and smooth sounding broadband or multiband compressor and low distortion final limiter round out the M2 to create powerful and authoritative presence on production or on-air microphones.

## Processing Presets

A variety of ready-to-use factory processing presets are provided, carefully tailored for different processing goals and formats. You can select a factory preset, confident that it will sound great just as it is. Or use a factory preset as a starting point and create a custom sound for each announcer, then save the new settings as a personalized user preset. In a facility with multiple microphone processors, presets saved in one unit can be easily copied to the others.




**Wheatstone Talent Control Interface and GUI**

Voice talent can activate his or her own personal sound at the press of a button using the Talent Control Interface, a special GUI designed for preset recall only. The Wheatstone Talent Control Interface software can reside on an air studio/control room PC and gives talent the ability to recall presets from any Wheatstone microphone processor without allowing processing adjustments. It also offers a high-resolution display of input and output levels as well as an FFT display of the talent’s voice either pre or post processing.

All parameters of the M2 are adjustable using the included Windows-based GUI which can control as many as 254 M-2 devices (see page 10).

- Extremely high performance microphone preamplifiers with 48V phantom power
- Two completely independent processing channels – may be operated as an M/S pair
- All digital, field proven Wheatstone-designed advanced processing algorithms
- Phase Rotator to correct asymmetrical voice waveforms
- High- and low-pass filters as well as an adjustable High-Q notch filter
- Fully adjustable downward expander
- Precision de-esser sibilance controller
- Four-bands of EQ: low-frequency shelving, two-band parametric, high-frequency shelving
- Compressor: broadband, two, or three bands
- Final precision peak limiter – can be defeated if desired
- TCP/IP-based remote control from anywhere via Vorsis Remote Control Software
- Talent Control Interface software for preset recall without processor control
- Password controlled access and control-less front panel for keeping settings secure
- Full metering of input and output levels and all signal processing
- FFT and oscilloscope displays of pre and post processing audio
- Requires only one rack space



# M4-IP(3) 4-channel mic/voice preamp/processor

dramatic Vorsis sound improvement in a full-function WheatNet-IP BLADE or BLADE-3



Available as an original BLADE (M4-IP) or as a new BLADE-3 (M4-IP3), this is a one rack unit with four completely independent DSP-based high quality voice/mic processors that are available standalone from the unit or accessible from anywhere in your WheatNet-IP network.

The M4-IP Microphone Processor combines four high-quality microphone preamps, four channels of Vorsis Embedded microphone processing, and a WheatNet-IP BLADE interface, allowing you to place four microphone inputs anywhere in your WheatNet-IP Intelligent Network (although it also works just fine as a standalone processor). The preamps and processors are accessed and controlled from any point on the network via its Windows-based GUI.

The M4-IP is a great way to maximize your investment in on-air talent by combining four mic processors into a single rack space, accessible from anywhere.

The M4-IP microphone processor is equipped with four matched Super-Quiet (SQ) microphone preamplifiers featuring an extremely low noise floor, very wide dynamic range, faithfully accurate transient response, and ruler flat frequency response. Operating in harmony with high quality 24-bit A/D converters and a 96kHz base sample rate, the M4-IP adds absolutely no undesired coloration to the signal and faithfully preserves the sound of any microphone and talent combination. It also features a four-section equalizer with high and low shelving EQ and two bands of fully parametric EQ, high and low pass filters, and de-esser and expander functions.

The signal path of the M4-IP includes four completely independent channels of Wheatstone's smooth-sounding Vorsis dynamics processing. Adjustable from anywhere on your network, the M4-IP offers the security of password protected TCP/IP-based remote control and no front panel controls.

## Wheatstone-designed Equalization

Based on great-sounding designs built for Wheatstone's other high performance professional audio applications, the M4-IP's equalization section operates predictably and adds no noise, ringing, phasiness or other undesirable coloration to the sound.

## Wheatstone-designed Dynamics Processing tools

A high performance and fully adjustable downward expander, de-esser, and smooth sounding broadband compressor and selectable low distortion final look-ahead limiter round out the M4-IP to create powerful and authoritative presence to production or on-air microphones.

## Processing Presets

A variety of ready-to-use factory processing presets are provided, carefully tailored for different processing goals and formats. You can select a factory preset, confident that it will sound great just as it is. Or use a factory preset as a starting point and create a custom sound for each announcer, then save the new settings as a personalized user preset. In a facility with multiple microphone processors, presets saved in one unit can be easily copied to the others.

## WheatNet-IP Native

The M4-IP is a WheatNet-IP BLADE which gives it a great deal of additional functionality. All Wheatstone's BLADEs are single rack-space interfaces that talk directly to WheatNet-IP control surfaces, other BLADEs and compatible third-party equipment. They contain features such as router control, logic control, gain control, two 8-channel utility mixers, silence detection and switching (among other things).



#### Wheatstone Talent Control Interface and GUI

Voice talent can activate his or her own personal sound at the press of a button using the Talent Control Interface, a special GUI designed for preset recall only. The Wheatstone Talent Control Interface software can reside on an air studio/control room PC and gives talent the ability to recall presets from any Wheatstone microphone processor without allowing processing adjustments.

All parameters of the M4-IP are controlled using the included Windows-based GUI (see page 10).

- Four extremely high performance microphone preamplifiers with 48V phantom power
- Four completely independent processing channels
- Four stereo analog line level outputs
- Four stereo AES outputs
- All digital, field proven Wheatstone-designed advanced processing algorithms
- Phase Rotator to correct asymmetrical voice waveforms
- High- and low-pass filters
- Fully adjustable downward expander
- Precision de-esser sibilance controller
- Four-bands of EQ: low-frequency shelving, two-band parametric, high-frequency shelving
- Broadband compressor
- Final precision peak limiter – can be defeated if desired for lower latency
- TCP/IP-based remote control from anywhere via M4-IP Remote Control Software
- Talent Control Interface software for preset recall without processor control
- Password controlled GUI access
- Front panel metering of input and output levels
- WheatNet-IP BLADE with full BLADE features including:
  - 12 Universal Logic ports (GPIO)
  - Front panel headphone jack
  - Front panel LED bargraph metering
  - Built-in routing control
  - Two built-in 8-channel utility mixers
  - Gigabit Ethernet
  - Silence sensing can be applied to any output
- BLADE-3 option adds AES67 compatibility, front panel logic indicators, LIO/SLIO logging, aliases, associated connections, dual OLED displays, clock/sync indicators and more

# the bigger picture

our GUIs give you the tools needed to dig in and OWN the sound of your voice



## M-1 & M-2 Control Software

The Vorsis Control Software – separate versions for each of the voice processors – loads on an external PC. You can connect the PC directly to the processor, or install the processor on your station's Ethernet LAN and access it from anywhere in your network (or remotely over VPN).

With Vorsis Control Software no adjustment is more than two mouse clicks away. And unlike other processors, every processing control is available and labeled for exactly what it does, giving you ultimate power to create your ideal sound.

The remote control screen is divided into an upper control area and a lower dynamic section that includes real-time display of gain reduction as well as a frequency-domain graph that shows the spectral characteristics of your audio. Every screen also includes accurate metering of input and output peak and average levels. Tabs across the top of the GUI software allow immediate access to each section of the processing - parametric EQ, de-esser, filters, compressor and downward expander.



## M4-IP Control Software

For the M4-IP, the control screen has tabs for each of its four channels, making it exceptionally quick and easy to set up each of your announcers and see the differences in the settings.

You have control over parametric EQ, de-esser, filters, compressor and downward expander. There are also high and low pass filters and an overall output limiter (so you are ready if a screamer steps behind the mic).

M4-IP's Vorsis Control Software runs on an external PC and can be controlled remotely from anywhere there is an internet connection.



# the nitty gritty

specifications and other little things that make the difference



## FACTORY PRESETS

Factory presets are pre-installed and write protected. New factory presets can be downloaded from the [Wheatstone-Processing.com](http://Wheatstone-Processing.com) web site and installed via the Windows-based GUI software.

## USER PRESETS

M-1: unlimited preset storage on the host PC  
 M-2: storage for 80 presets in on-board non-volatile memory, unlimited storage on host PC.  
 M-4: storage for 80 presets in on-board non-volatile memory, unlimited storage on host PC.

## AUDIO INPUTS

Microphone XLR-F connector (one on M-1, two on M-2, four on M-4)  
 Electronic differential >2KΩ (bridging)  
 Optimum source impedance 200Ω  
 Phantom Power 48VDC, switchable on/off  
 Gain -10dB to +70dB in 1dB steps  
 Frequency response ±0.2dB 20Hz-20KHz  
 Equivalent input noise (EIN) -128dBu  
 THD+N <0.03%, 20Hz-20kHz, -50dBu input  
 SMPTE DIM 0.00007%

## AUDIO OUTPUTS

Mic or line level output selectable (M-1 only)  
 Line-level output (M-2 and M-4 only)  
 Digital XLR-M connector (one on M-1, two on M-2)  
 Two RJ45 to StudioHub standard (M-2 and M-4 only)  
 Reference Level: 0VU=-20dBFS  
 Output Sample Rates:  
 M-1: 44.1 kHz, 48 kHz and 96 kHz  
 M-2: 48 kHz fixed  
 M-4: 44.1kHz or 48kHz  
 Balanced 110Ω AES-3 0VU=-20dBFS  
 Analog XLR-M connector (one on M-1, two on M-2)  
 Electronically balanced <10Ω source impedance  
 Optimum load impedance >600Ω  
 Maximum output level +24dBu

## FILTERS

Asymmetry filter Phase rotator, 4th order allpass, switchable in/out  
 High-pass 24dB/octave Butterworth  
 Adjustable 20Hz-1kHz  
 Low-pass 24dB/octave Butterworth  
 Adjustable 1-20kHz  
 Notch (M-2 only) Fixed bandwidth  
 Adjustable 20Hz-20kHz

## DOWNWARD EXPANDER

Threshold Adjustable -60dBFS to 0dBFS  
 Depth Adjustable 0-40dB  
 Close Adjustable 50ms-3s

## DE-ESSER

Control Recursive-style  
 Threshold Adjustable -10dBFS to -60dBFS  
 Attack time (M-2 only) Adjustable 0.1ms-100ms  
 Release time Adjustable 50ms-500ms  
 De-ess frequency Adjustable 20Hz-20kHz  
 Bandwidth (M-2 only) Adjustable 0.15-4 octave

## PARAMETRIC EQUALIZER

Routable Pre or post compressor  
 Band 1 Shelving  
 Adjustable 20-200Hz  
 Boost/cut ±14dB  
 Bands 2 and 3 Parametric  
 Adjustable 20Hz-20kHz  
 Boost/cut ±14dB  
 Bandwidth 0.2-3.0 octave  
 Band 4 Shelving  
 Adjustable 2kHz-20kHz  
 Boost/cut ±14dB

## COMPRESSOR – M-1 and M-4

Control Broadband  
 Threshold -10dBFS to -50dBFS  
 Attack time 0.2ms-1s  
 Release time 33ms-1s  
 Ratio 1:1-20:1

## COMPRESSORS – M-2

One, two, or three processing bands  
 Crossover frequencies:  
 Band 1-2 adjustable 20Hz-1kHz  
 Band 2-3 adjustable 1kHz-20kHz  
 Threshold 10 to -50dBFS  
 Attack time 0.2ms-1s  
 Release time 33ms-1s  
 Ratio 1:1-20:1

## FINAL LIMITER (M-2 and M-4 only)

Control Zero-overshoot look-ahead limiter  
 Threshold -50 to -10dBFS (fixed at -6dBFS in M-4)  
 Attack 0-100ms (automatic in M-4)  
 Release 10ms-330ms (automatic in M-4)

## LOGIC I/O, M-1 and M-2

Remote control RJ45 connector (two on M-2)  
 For M-1 and M-2 Optional Wheatstone Announcer Panel or custom interface  
 Connections ON, OFF, Cough, ON tally, OFF tally, power and ground  
 GPI input (M-2 only) DB9 connector  
 Eight opto-isolated ports for external switching of presets (M-2 only)

## LOGIC I/O, M-4

12 opto-isolated and fully configurable GPIO logic ports

## CONTROL

M-1 and M-2 Ethernet 10-100BASE-T, RJ45 connector  
 M-4 1000BaseT Gigabit Ethernet

## PHYSICAL - M-1

Dimensions 19"/48.3cm wide  
 1.75"/4.5cm high  
 10"/25.4cm deep  
 (allow 3.25"/8.25cm for rear connectors)  
 Weight 8.1lbs/3.68kg  
 Shipping weight 13lbs/5.9kg  
 Power Requirements 90-260VAC, 50-60Hz, 24VA

## PHYSICAL - M-2

Dimensions 19"/48.3cm wide  
 1.75"/4.5cm high  
 16"/40.6cm deep  
 (allow 3.25"/8.25cm for rear connectors)  
 Weight 11.35lbs/5.16kg  
 Shipping weight 15lbs/6.8kg  
 Power 90-260VAC, 50-60Hz, 19VA

## PHYSICAL - M-4

Dimensions 19"/48.3cm wide  
 1.75"/4.5cm high  
 13.25"/33.7cm deep  
 (15.25"/38.7cm deep w/rear connectors)  
 Weight 10.35lbs/4.69kg  
 Shipping weight 14lbs/6.4kg  
 Power 90-120VAC, 50-60Hz, 22VA



Designed and built by  
 Wheatstone Corporation  
 600 Industrial Drive | New Bern NC 28562-5440 USA  
 phone 1.252.638-7000 | fax 1.252.635-4857  
 wheatstone.com | sales@wheatstone.com

**Wheatstone**  
 BROADCAST AUDIO PERFECTIONISTS®